

---

**RMA 160****TYPICAL PROPERTIES****TECHNICAL DATA SHEET**

<b>Appearance</b>	<b>Free Flowing</b>
<b>Visual Observation</b>	<b>White Powder</b>
<b>K-Value</b>	<b>52</b>
<b>Inherent Viscosity (ASTM D 1243-79)</b>	<b>0.55</b>
<b>Volatiles (% maximum) (ASTM D3030-79)</b>	<b>0.3</b>
<b>Apparent Bulk Density (g/cc) (ASTM D189-69)</b>	<b>0.52</b>
<b>Specific Gravity</b>	<b>1.3</b>
<b>Particle Size (ASTM D1921-63)</b>	
Through 40 mesh (% minimum)	<b>100</b>
Through 200 mesh (% maximum)	<b>15</b>
<b>ASTM Cell Classification (ASTM D1755)</b>	<b>GP2-16430 GP1-16030</b>

---

**Disclaimer**

*This information is considered accurate and reliable as of the date appearing above and is presented in good faith. Because use conditions and applicable laws may differ from one location to another and may change with time, Recipient is responsible for determining whether the information in this document is appropriate for recipient's use. Since RMA has no control over how this information may be ultimately used, all liability is expressly disclaimed and RMA assumes no obligation or liability therefore. No warranty, express or implied, is given nor is freedom from any patent owned by RMA or others to be inferred.*